

PRODUCT SPECIFICATION SHEET

AZOMITE® FEED GRIT



FEED INGREDIENT

Hydrated Sodium Calcium Aluminosilicate

Anticaking agent

Do not exceed 2% of the feed mixture in accordance with good feed mixing and manufacturing practices.

TYPICAL SPECIFICATIONS

Parameter	Specification
Moisture wt. %	<8%
Bulk Density (loose)	67.45 lb/ft ³ or 1,080.45 kg/m ³
Bulk Density (rodded)	75.86 lb/ft ³ or 1,215.16 kg/m ³
Size	Passing #8 Sieve (<2.38mm)
Angle of Repose (degrees)	39 degrees



AZOMITE® at a glance

- AZOMITE® is a sized natural material
- It's 100% natural and completely free from fillers.
- Listed by Organic Materials Review Institute (OMRI) for use in certified organic production.
- Approved California organic input material.
- AZOMITE® is a hydrated sodium calcium aluminosilicate (HSCAS) containing minerals.

The Safety Data Sheet for this product contains important environmental, health, and safety information regarding this product, including information concerning the handling and storage of this product. Copies of the SDS can be obtained at www.azomite.com or www.azomiteinternational.com or by contacting your AZOMITE® representative.

Effective January 2017 - Specifications are subject to change